



FEATURES

Simple installation, operation and maintenance

Affordable price

Detects movement

Narrow detection zone reduces false alarms

Can be installed adjacent to a bed or across a doorway

Magnetic mounting hardware (included with EzyStand)

On / Off switch to conserve battery life when not in use

Works with other cura¹ cordless receivers

Integrated speaker for stand-alone operation

EzyStand has adjustable height and clips for (optional) Plug Pack cable

S TECHNICAL SPECIFICATIONS

iBeam

Detection range: 5 m (approx.*)

Wireless range: 30 m*

Power supply: 6-12 V DC & / or 3 x AA alkaline batteries (included)

(DOES NOT INCLUDE 2721)

Battery life: 6 months with normal usage

Housing material: ABS plastic

Dimensions: 78 x 81.5 x 38.5 mm (includes bracket)

Weight: 100 g (not incl. batteries) Operating temp: -25°C to 55°C

Relative humidity: < 85%

Standby current consumption: 1 mA

Alarm condition current consumption: 20 mA

Operating frequency: 433 MHz (TX) (Not supervised)

Transmission strength: < 10 mW

EzyStand

Height: Adjustable from 650 mm to 885 mm PVC base and chrome plated stand

ACCESSORIES

3501 ActiveCare LCD Pager, 3508 ActiveCare LED Pager, 2700 Six Channel Cordless Falls Monitor, 3500 ActiveCare Console, 2544 Wireless Multiport Expander, 2549 Wireless Multiport Expander Bracket Mount, 2404 12 V Plug Pack

